



REPLACEMENT SHEET
S/N 10/761,045

1/31




FIG. 1




FIG. 2




FIG. 3





FIG. 4b









FIG. 5

3/31



4/31




FIG. 8







FIG. 9a

FIG. 9b

5/31



6/31





FIG.12

7/31




FIG. 13

8/31




FIG. 14

9/31




FIG. 15

+




FIG. 16






FIG. 17

+

11/31



12/31




FIG. 20a

13/31




FIG. 20b

+

14/31




FIG. 20c

15/31




FIG. 21





FIG. 22

16/31



17/31





FIG. 24

18/31






FIG. 25

19/31



20/31




FIG. 27

21/31




FIG. 28

22/31




FIG. 29

23/31




FIG. 30

24/31




FIG. 31

25/31




FIG. 32

26/31




FIG. 33

27/31




FIG. 34

28/31




FIG. 35




FIG. 36

29/31

900
↙

DISPOSE A TUBULAR WITHIN THE BOREHOLE, THE
TUBULAR INCLUDING A SLOTTED STATION AND
MEANS TO HYDRAULICALLY ISOLATE THE
TUBULAR INTERIOR FROM A SURROUNDING
BOREHOLE AT THE SLOTTED STATION, THE
TUBULAR ADAPTED TO RECEIVE A SENSOR OR
ANTENNA FOR MONITORING A FORMATION
CHARACTERISTIC

FIG. 37

+

30/31




FIG.29a

+

31/31

950




FIG.38